

WHAT IS CLAIMED IS:

5

1. A data transmission apparatus comprising:
a spread spectrum processing part that performs a
spread spectrum process on an input signal;
an analog-to-digital conversion part that performs
10 an analog-to-digital conversion process on a signal that
has undergone said spread spectrum process; and
an inverse spread spectrum processing part that
performs an inverse spread spectrum process of said spread
spectrum process on a signal that has undergone said
15 analog-to-digital conversion process.

20

2. The data transmission apparatus as claimed in
claim 1, wherein said spread spectrum process is performed
using a predetermined PN sequence.

25

3. The data transmission apparatus as claimed in
claim 2, wherein a PN sequence number of said PN sequence
is set to a value that is adequate for substantial
30 improvement in the precision of said analog-to-digital
conversion process so that transmission data contained in
the input signal can be detected with predetermined
precision.

35

4. The data transmission apparatus as claimed in claim 1, further comprising:

a gain controlling part that performs a signal gain controlling process on an input signal, wherein

5 said spread spectrum processing part performs a spread spectrum process on a signal that has undergone said signal gain controlling process.

10

5. A power line carrier communication system comprising:

15 a power line functioning as a data transmission path for transmitting data; and

a data transmission apparatus that terminates said power line, said data transmission apparatus comprising:

a spread spectrum processing part that performs a spread spectrum process on an input signal;

20 an analog-to-digital conversion part that performs an analog-to-digital conversion process on a signal that has undergone said spread spectrum process; and

25 an inverse spread spectrum processing part that performs an inverse spread spectrum process of said spread spectrum process on a signal that has undergone said analog-to-digital conversion process.

30

6. A data transmission method comprising:

a spread spectrum processing step of performing a spread spectrum process on an input signal;

35 an analog-to-digital conversion step of performing an analog-to-digital conversion process on a signal that has undergone said spread spectrum process; and

an inverse spread spectrum processing step of

performing an inverse spread spectrum process of said spread spectrum process on a signal that has undergone said analog-to-digital conversion process.

5

7. The data transmission method as claimed in claim 6, wherein said spread spectrum process is performed using a predetermined PN sequence in said spread spectrum processing step.

15

8. The data transmission method as claimed in claim 7, wherein a PN sequence number of said PN sequence is set to a value that is adequate for substantial improvement in the precision of said analog-to-digital conversion process so that transmission data contained in the input signal can be detected with predetermined precision.

25

9. The data transmission method as claimed in claim 6, further comprising:

a gain controlling step of performing a signal gain controlling process on an input signal; wherein

30 said spread spectrum process of said spread spectrum processing step is performed on a signal that has undergone said signal gain controlling process.